


ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

TDS of STRONGER FIBERGLASS SERIE YS6001S



| Product | Product Category | Coating |
|-------------------|---------------------------|---------|
| PTFE GLASS FABRIC | STRONGER FIBERGLASS SERIE | PTFE |

| Properties | Metric | Imperial |
|---|---------------------------|----------------------------|
| Standard width Please ask for other widths | 1000, 1500, 2000, 3000 mm | 39.5, 59, 78.7, 118 inches |
| Mesh Size | 1 x 1 mm | 0.0393 x 0.0393 inches |
| Fiberglass | Stronger Fiberglass | Stronger Fiberglass |
| Tensile Strength | 536 N/cm Warp | 306 lbs/inches Warp |
| | 410 N/cm Fill | 234 lbs/inches Fill |
| Color | Brown | Brown |
| Temperature resistance | -73 to +260 °C | -100 to +500 °F |

ESONE® stronger fiberglass series is using stronger fiberglass yarn for weaving, the tensile strength and lifetime is better than standard mesh series.

The main applications is screen printing, drying, packaging industry, textile industry, wood processing industry and so on, which is used as heat resistant and non stick conveyor belt to transport materials through ovens.

1x1 mm PTFE open mesh fabric is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by
 Jiangsu Esoner New Material Co.,Ltd
 Taixing Youngsun FL-Plastics Co.,Ltd
 Western End of South Third Ring Road, Taixing, Jiangsu, China
 Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com

www.ptfe-fabrics.com