


# ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

## TDS of STRONGER FIBERGLASS SERIE YS6008S



Product	Product Category	Coating
PTFE GLASS FABRIC	STRONGER FIBERGLASS SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1400, 2500, 2600, 2700, 3300, 3400, 3700, 3800, 4000 mm	39.5, 55, 98.4, 102, 106, 130, 134, 146, 150, 158 inches
Mesh Size	4x4 mm	4x4 mm
Weight	720 g/m <sup>2</sup>	21.2 oz/yd <sup>2</sup>
Fiberglass	Stronger Fiberglass	Stronger Fiberglass
Tensile Strength	405 N/cm Warp	231 lbs/inches Warp
	640 N/cm Fill	366 lbs/inches Fill
Color	Brown	Brown
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® stronger fiberglass series is using stronger fiberglass yarn for weaving, the tensile strength and lifetime is better than standard mesh series.

The main applications is screen printing, drying, packaging industry, textile industry, wood processing industry and so on, which is used as heat resistant and non stick conveyor belt to transport materials through ovens.

4x4 mm PTFE open mesh fabric is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by  
 Jiangsu Esoner New Material Co.,Ltd  
 Taixing Youngsun FL-Plastics Co.,Ltd  
 Western End of South Third Ring Road, Taixing, Jiangsu, China  
 Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com