


# ESONE®

PTFE & Silicone Coated Fiberglass Fabric & Belt

## TDS of OPEN MESH SERIE YS6011



Product	Product Category	Coating
PTFE GLASS FABRIC	OPEN MESH SERIE	PTFE

Properties	Metric	Imperial
Standard width Please ask for other widths	1000, 1500, 2500, 2700, 3200, 3800, 4000 mm	39.5, 59, 98.4, 106, 126, 150, 158 inches
Mesh Size	4 x 4 mm	0.1574 x 0.1574 inches
Weight	580 g/m <sup>2</sup>	17.1 oz/yd <sup>2</sup>
Weft	Double weft	Double weft
Tensile Strength	330 N/cm      Warp	189 lbs/inches      Warp
	470 N/cm      Fill	269 lbs/inches      Fill
Color	White	White
Temperature resistance	-73 to +260 °C	-100 to +500 °F

ESONE® open mesh series, PTFE coated mesh belt is coated with high quality PTFE resin, the basic material is woven open mesh fiberglass or aramid fabric (like Kevlar) or Nomax. The main applications is screen printing, drying industry, packaging industry, textile industry, wood processing industry and so on, which is used as heat resistant and non stick conveyor belt to transport materials through ovens. 4x4mm PTFE open mesh fabric is FDA & LFGB certificated, can be used in direct contact with food.



ESONE® is a registered trademark owned by  
 Jiangsu Eson New Material Co.,Ltd  
 Taixing Youngsun FL-Plastics Co.,Ltd  
 Western End of South Third Ring Road, Taixing, Jiangsu, China  
 Tel: 0523-87590206 E-Mail: sales@chinayoungsun.com